



Models	Capacity GusPM [LPM]	Wall thickness in [mm]	A Inlet and outlet	B Bottom to center in [mm]	C* Center to top in [mm]	D Width in [mm]	E Length in [mm]	F* Height in [mm]
CA-IS35-E	35 [132]	1/2 [13]	DN 4 po	15 [381]	12 [305]	25 [635]	28 [711]	27 [686]
CA-IS50-E	50 [189]	1/2 [13]	DN 4 po	17 [432]	12 [305]	25 [635]	28 [711]	29 [737]
CA-IS75-E	75 [284]	3/4 [19]	DN 4 po	19 [483]	12 [305]	29 [737]	31 [787]	31 [787]
CA-IS100-E	100 [378]	3/4 [19]	DN 4 po	23 [584]	12 [305]	34 [864]	43 [1092]	35 [889]
CA-IS150-E	150 [568]	3/4 [19]	DN 4 po	25 [635]	12 [305]	42 [1067]	56 [1422]	37 [940]
CA-IS200-E	200 [757]	3/4 [19]	DN 4 po	30 [732]	12 [305]	44 [1118]	61 [1549]	42 [1067]
CA-IS250-E	250 [946]	3/4 [19]	DN 4 po	36 [914]	12 [305]	52 [1321]	71 [1803]	48 [1219]

Note: Larger capacity available on request. * Dimension "C" can vary according to needs and dimension "F" will be modified in consequence.

DESCRIPTION

Built-in polypropylene solids interceptor including fixed baffle retaining solids, inversed "T" equipped with a cleanout and a slip-resistant bolted aluminum cover with sealing liner.

OPTIONS

- ☐ **E** Extension (C ___ and F measurement will vary)
- ☐ **CES** Cover frame with high quality neoprene gasket

- ☐ **CR** Reinforced cover
- ☐ **SS** Stainless steel cover