

DESCRIPTION

Metering push-button shower system in recessed cabinet 229 x 229 x 102 mm (9 x 9 x 4 in) with 18 gauge stainless steel faceplate. Includes hydropneumatic valve with forged brass body and stainless steel seat, service stop with incorporated filter, chrome brass plated push-button mounted on front panel, automatic shut-off, 10 to 60 seconds adjustable cycle, type 304, 18 gauge, polished satin finish stainless steel faceplate measuring 279 x 279 mm (11 x 11 in), 4 vandal resistant stainless steel screws, flexible connecting tubing from the valve to the actuator, pre-mixed water supply, DN 1/2 in fem. inlet and outlet. Includes gasket. Push-button conforms to ADA requiring less than 5 lbs (2.2 kg) pressure to operate.

Note: Possibility to install the hydropneumatic valve at a maximum distance of 3 m (10 feet) of the push-button actuator (ex: in a suspended ceiling). In this case, a faceplate of 152 x 152 mm (6 x 6 in) or 102 x 102 mm (4 x 4 in) may be used for the push-button actuator. Access to the hydropneumatic valve must be provided.



Meet standards:
 ASME A112.18.1
 ASME A112.18.11 (2012)
 CSA B125.1 (2005)
 CSA B125.1 (2012)

Note: CSAB125.1 (ASSE1069) certified thermostatic mixing valve is required, see Leonard Valve Company 269LF, 369LF, and/or XL690. To be selected according to the number of showers.

