



Models	Capacity Guspm [LPM]	A Inlet and outlet	B Bottom to center in [mm]	C* Center to top in [mm]	D Width in [mm]	E Length in [mm]	F* Height in [mm]	G Waste oil recovery tank capacity Gallons [L]
CA-SH25-20	25 [95]	DN 3 po	14 [356]	12 [305]	35 [889]	24 [610]	26 [661]	20 [76]
CA-SH35-25	35 [132]	DN 4 po	15 [381]	12 [305]	40 [1016]	28 [711]	27 [686]	25 [95]
CA-SH50-30	50 [189]	DN 4 po	17 [432]	12 [305]	40 [1016]	28 [711]	29 [737]	30 [113]
CA-SH75-35	75 [284]	DN 4 po	19 [483]	12 [305]	44 [1118]	31 [787]	31 [787]	35 [132]
CA-SH100-50	100 [378]	DN 4 po	23 [584]	12 [305]	46 [1168]	43 [1092]	35 [889]	50 [189]
CA-SH150-75	150 [568]	DN 4 po	25 [635]	12 [305]	55 [1397]	56 [1422]	37 [940]	75 [284]
CA-SH200-120	200 [757]	DN 4 po	30 [762]	12 [305]	57 [1448]	61 [1549]	42 [1067]	120 [454]
CA-SH250-125	250 [946]	DN 4 po	36 [914]	12 [305]	57 [1448]	74 [1880]	48 [1219]	125 [473]
CA-SH300-150	300 [1136]	DN 6 po	39 [622]	12 [305]	60 [1524]	76 [1930]	51 [1295]	150 [568]

*Note: Larger capacity available on request. * Dimension "C" can vary according to needs and dimension "F" will be modified in consequence.*

DESCRIPTION

Polypropylene oil interceptor with integrated waste oil recovery tank. The interceptor will include a flow regulator and removable baffle, a fixed baffle retaining solids, water seal equipped with a cleanout and a slip-resistant aluminum cover.

OPTIONS

- | | |
|--|--|
| <input type="checkbox"/> SS 304 stainless steel cover | <input type="checkbox"/> CES Cover frame with high quality sealquality seal |
| <input type="checkbox"/> CRG Reinforced cover made of galvanized steel | <input type="checkbox"/> DH Oil detector and control panel |
| <input type="checkbox"/> DH-CS Dry contact oil detector and control panel | <input type="checkbox"/> CR Reinforced cover |
| <input type="checkbox"/> RS Suction connection | <input type="checkbox"/> PS Sediment bucket |
| | <input type="checkbox"/> RS2 2 Suction connections |